











Digital Microprocessor Controller



#### RLCG0100 Refrigerated Cooled Incubator Glass Door

This 88 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel exterior and stainless steel interior and fully adjustable shelves, this incubator is versatile and built to last.

Complete with an access port and internal light this incubator offers temperature precision of better than  $\pm 0.5$  °C at 4°C and  $\pm 1$ °C at 20°C.

Part Number	RLCG0100
Capacity (Litres)	88
Style	Benchtop
Exterior Dimensions (HxWxD)	860 x 500 x 535mm
Interior Dimensions (HxWxD)	565 x 420 x 335mm
Weight	40kg
Energy Consumption	2kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Stainless Steel
Exterior Construction	<b>Enamelled Steel</b>
Door Style	Glass
Door Hinging	Right
Shelves	2
Shelf dimension (WxD)	330 x 410 mm
Spare shelves available	$\checkmark$
Internal Light	$\checkmark$
Temperature display	$\checkmark$
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	Х
Eco Friendly Refrigerant	✓





















**Access Port** 



Door Lock



Digital Microprocessor Controller

Most models have the choice of glass or solid door

### RLSD01502 Refrigerated Cooled Incubator

This 150 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel exterior and powder coated steel interior and fully adjustable shelves, this incubator is versatile and built to last with a temperature uniformity of better than  $\pm 0.5$ °C at 4°C and  $\pm 1$ °C at 20°C

This model is also available with a glass door, please see **Labcold** model RLCG0502.

Part Number	RLSD01502
Capacity (Litres)	150
Style	Underbench
Exterior Dimensions (HxWxD)	820 x 600 x 600mm
Interior Dimensions (HxWxD)	690 x 510 x 430mm
Weight	43kg
<b>Energy Consumption</b>	2kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Powder Coated Steel
<b>Exterior Construction</b>	<b>Enamelled Steel</b>
Door Style	Solid
Door Hinging	Right
Lock	Manual Key
Shelves	3
Shelf dimension (WxD)	495 x 3200mm
Spare shelves available	✓
Internal Light	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	Х
Eco Friendly Refrigerant	√





















**Access Port** 



Door Lock



Digital Microprocessor Controller

Most models have the choice of glass or solid door

### RLCG01502 Refrigerated Cooled Incubator Glass Door

This 150 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel exterior and powder coated steel interior and fully adjustable shelves, this incubator is versatile and built to last with a temperature uniformity of better than  $\pm 0.5$ °C at 4°C and  $\pm 1$ °C at 20°C.

This model is also available with a glass door, please see **Labcold** model RLCG0502.

Part Number	RLCG01502
Capacity (Litres)	150
Style	Underbench
Exterior Dimensions (HxWxD)	820 x 600 x 600mm
Interior Dimensions (HxWxD)	690 x 510 x 430mm
Weight	43kg
<b>Energy Consumption</b>	2kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Powder Coated Steel
<b>Exterior Construction</b>	<b>Enamelled Steel</b>
Door Style	Glass
Door Hinging	Right
Lock	Manual Key
Shelves	3
Shelf dimension (WxD)	495 x 3200mm
Spare shelves available	✓
Internal Light	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	Х
Eco Friendly Refrigerant	✓





















Digital Microprocessor Controller

Most models have the choice of glass or solid door

### RLCG0300 Refrigerated Cooled Incubator Glass Door

This 300 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel interior and exterior and fully adjustable shelves, this incubator is versatile and built to last with temperature uniformity of better than  $\pm 0.5$ °C at 4°C and  $\pm 1$ °C at 20°C.

This model is also available with a solid door, please see

Labcold model RLSD0300

Part Number	RLCG0300
Capacity (Litres)	300
Style	Freestanding
Exterior Dimensions (HxWxD)	1487 x 600 x 650mm
Interior Dimensions (HxWxD)	1360 x 500 x 400mm
Weight	75kg
Energy Consumption	0.9kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Powder Coated Aluminium
Exterior Construction	<b>Enamelled Steel</b>
Door Style	Glass
Door Hinging	Right
Lock	Manual Key
Shelves	3
Shelf dimension (WxD)	495 x 460mm
Spare shelves available	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	Х
Eco Friendly Refrigerant	✓





















Digital Microprocessor Controller

Most models have the choice of glass or solid door

### RLSD0300 Refrigerated Cooled Incubator

This 300 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel interior and exterior and fully adjustable shelves, this incubator is versatile and built to last with a temperature uniformity of better than  $\pm 0.5$ °C at 4°C and  $\pm 1$ °C at 20°C.

This model is also available with a glass door, please see **Labcold** model RLCG0300

Part Number	RLSD0300
Capacity (Litres)	300
Style	Freestanding
Exterior Dimensions (HxWxD)	1487 x 600 x 650mm
Interior Dimensions (HxWxD)	1360 x 500 x 400mm
Weight	75kg
Energy Consumption	0.9kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Powder Coated Aluminium
<b>Exterior Construction</b>	<b>Enamelled Steel</b>
Door Style	Solid
Door Hinging	Right
Lock	Manual Key
Shelves	3
Shelf dimension (WxD)	495 x 460mm
Spare shelves available	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	Х
Eco Friendly Refrigerant	<b>✓</b>















This 570 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

Digital Microprocessor Controller



With a robust stainless steel interior, enamelled steel exterior and fully adjustable shelves, this incubator is versatile and built to last.

# RLSD0600 Refrigerated Cooled Incubator

Part Number	RLSD0600
Capacity (Litres)	570
Style	Freestanding
Exterior Dimensions (HxWxD)	1980 x 720 x 840mm
Interior Dimensions (HxWxD)	1405 x 600 x 570mm
Weight	140kg
Internal Light	LED
Temperature Uniformity	±0.5°C at 4°C ±1.0°C at 20°C
Operating Temperature	+5°C to +40°C
Interior Construction	Stainless Steel
Exterior Construction	Enamelled Steel
Door Style	Solid
Door Hinging	Right
Inner Doors	2
Shelves	4
Shelf dimension (WxDxH)	580 x 530 x 15mm
Spare shelves available	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	X
Alarm	Optional Extra
Eco Friendly Refrigerant	<b>V</b>

Labcold Cooled Incubators are also available in 88 litre, 150 litre and 600 litre capacity

Most models have the choice of glass or solid door















This 570 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

Digital Microprocessor Controller



With a robust stainless steel interior, enamelled steel exterior and fully adjustable shelves, this incubator is versatile and built to last.

# RLCG0600 Refrigerated Cooled Incubator

Part Number	RLCG0600
Capacity (Litres)	570
Style	Freestanding
Exterior Dimensions (HxWxD)	1980 x 720 x 840mm
Interior Dimensions (HxWxD)	1405 x 600 x 570mm
Weight	140kg
Internal Light	LED
Temperature Uniformity	±0.5°C at 4°C ±1.0°C at 20°C
Operating Temperature	+5°C to +40°C
Interior Construction	Stainless Steel
<b>Exterior Construction</b>	<b>Enamelled Steel</b>
Door Style	Glass
Door Hinging	Right
Inner Doors	2
Shelves	4
Shelf dimension (WxDxH)	580 x 530 x 15mm
Spare shelves available	✓
Temperature display	✓
Microprocessor controlled temperature regulation	√
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	X
Alarm	Optional extra

Labcold Cooled Incubators are also available in 88 litre, 150 litre and 600 litre capacity

Most models have the choice of glass or solid door



